


TEMPERATURE CONTROLS

Totaline & BRline Thermostats



MODEL : TTL-001 ELECTRONIC ROOM THERMOSTAT

- Accurate Setting
- Reliable
- 3 minute delay included
- LED light show status
- Fuse protection for safety
- Circuit surge protection MOV
- Easy to use and easy to install



MODEL : TTL-003 REMOTE CONTROLLER SET

- Use for Mini-Split ,Duct type and Chiller system
- 3 speed fan
- Sleep mode
- Watchdog diagram
- 3 minute delay
- Non Volatile memory
- self diagnostic



MODEL : TTL-004 DIGITAL ROOM THERMOSTAT

- LED digital temperature display
- Power on -off
- 3 speed fan
- Temperature setting
- Sensor error alarm
- Compressor delay protection
- Auto Reset
- Sweep motor (for model DR 01 to DR 04 only)
- 7 Mode for setting
- Use for Mini split ,Duct type and Chiller system



MODE	MODE OF OPERATION	COOLING / HEATING	COMPRESSOR DELAY
01	cool + sweep	Compressor	yes
02	cool + sweep	Chilled water	no
03	cool - fan - dry	Compressor	yes
04	cool - fan - dry	Chilled water	no
05	cool - fan - dry - heat - auto	Compressor / Heat pump	yes
06	cool - fan - dry - heat - auto	Compressor / Electric heater	yes ,only for cool
07	cool - fan - dry - heat - auto	hot / Chilled water	no

Totaline & BRline Thermostats



MODEL TTL-005 WALL THERMOSTAT (Carrier / Totaline)

is a two pieces fan coil thermostat available for Cool & Heat / Cool application. Stylish flat panel design display unit for mini-split, duct type or chilled water system. Display unit is designed to install with 2"x4" flush mounted electrical junction box.

Features

- 7 segment LED digital temperature display
- Capacitive touch sensing technology for all buttons
- Use only 2 wire cable between main and display unit
- 3 fan speeds
- Temperature setting
- Compressor / Valve status display
- Compressor time delay
- Auto reset
- System protection
- Self diagnostic
- Support on Carrier & Totaline Brand



TTL-005

MODEL TTL-006 MULTI STAGE THERMOSTAT

is a single piece thermostat for the control of 2 stage cooling or 2 stage electric heater (optional)

Features

- LED digital temperature display
- Power on / off
- Temperature setting
- Single fan speed relay output
- Dead band temperature setting
- Programmable of compressor time delay



TTL-006

NEW

MODEL TTL-008 + JBRM002 REMOTE CONTROLLER SET

- Use for Mini Split ,Duct type and Chiller system
- 3 Speed fan
- Sleep mode
- Temperature setting 18-30 Degree C
- Auto Restart
- Time Delay
- Self Diagnostic



TTL-008 + JBRM002