

# SCROLL COMPRESSOR FOR AIRCONDITIONING R-22



Model	Nominal HP	Capacity		Input Power (w)	Current (A)	COP W/W	EER Btu/Wh	Weight kg
		w	Btu/h					

### Electrical 50 Hz : 220-240 Volt : 1 Phase

ZR22K3 PFJ	1.8	5,350	18,200	1,730	8.0	3.08	10.5	25.9
ZR24K3 PFJ	2.0	5,900	20,200	1,920	9.2	3.08	10.5	25.0
ZR26K3 PFJ	2.2	6,350	21,700	2,010	9.5	3.17	10.8	27.2
ZR28KM PFZ	2.3	6,750	23,000	2,020	9.2	3.34	11.4	19.4
ZR30KM PFZ	2.5	7,350	25,000	2,190	10.1	3.34	11.4	19.3
ZR30KS PFZ	2.5	7,350	25,000	2,230	10.2	3.28	11.2	22.1
ZR32KS PFZ	2.7	7,900	27,000	2,410	10.9	3.28	11.2	22.1
ZR34K3 PFJ	2.8	8,250	28,100	2,550	12.1	3.22	11.0	28.6
ZR36K3 PFJ	3.0	8,850	30,200	2,720	13.1	3.25	11.1	29.5
ZR40K3 PFJ	3.3	9,750	33,300	3,000	14.7	3.25	11.1	27.9
ZR42K3 PFJ	3.5	10,250	35,000	3,150	15.2	3.25	11.1	30.4
ZR45K3 PFJ	3.8	11,200	38,200	3,380	16.4	3.31	11.3	32.2
ZR47K3 PFJ	3.9	11,550	39,400	3,460	16.8	3.34	11.4	31.3
ZR48K3 PFJ	4.0	11,850	40,500	3,630	17.6	3.28	11.2	31.3
ZR61KC PFZ	5.1	14,950	51,000	4,550	21.7	3.28	11.2	42.6
ZR68KC PFJ	5.7	16,700	57,000	5,130	24.5	3.25	11.1	40.4